



MAIN FEATURES

Rated current (with wiring 70 mm ²)	200 A	Câblage Flexible	70 mm ²
Maximum voltage	750 V	Câblage Stranded	70 mm ²
IP protection lid closed	IP65	Other wiring	on request
IP protection connected plug	IP65/IP66	Keying positions	12
Shock resistance	IK10	Protection mode	de
Ambient temperature	-40 °C to +60 °C	ATEX zones	1 & 2, 21 & 22

EACH SOCKET OUTLET OR INLET
MUST BE ASSOCIATED WITH A
BOX, A SLEEVE OR A HANDLE.

**SOCKET-
OUTLET** female
DX2 (200 A)



**INCLINED
APPLIANCE INLET**
male **DX2 (200 A)**



PLUG
male
DX2 (200 A)



Voltage 50 Hz	Polarity	Part no.	Part no.	Part no.
380 - 440 V	3P+E	2674013	2676013	36-48mm 2671013
380 - 440 V	3P+N+E	2674017	2676017	36-48mm 2671017

► Other voltages, frequencies and contact configurations are available (see page 10).

BOXES

Ex metal cable gland
included



Wall box
metal 90°

HANDLES

Ex metal cable gland
included



Straight handle
metal

Cable gland entry	Part no.	Cable gland entry	Part no.
M63	267AB53	M63	267A963
			36-48 mm

MARECHAL ELECTRIC MAROMME

 II 2 G D Ex de IIC tD A21

-40 °C ≤ Ta ≤ +60 °C T3 T91 °C

IECEX LCI 09.0015 / LCIE 04 ATEX 6038

LOCKING

Locking position connected or disconnected by lockable shaft as standard.