



MAIN FEATURES

Rated current (with wiring according to standard)	63 A	Flexible wiring (min-max)	16 - 50 mm ²
Maximum voltage	750 V	Stranded wiring (min-max)	16 - 50 mm ²
IP protection lid closed	IP65	Other wiring	on request
IP protection connected plug	IP65/IP66	Keying positions	12
Shock resistance	IK10	Protection mode	de
Ambient temperature	-40 °C to +60 °C	ATEX zones	1 & 2, 21 & 22

EACH SOCKET OUTLET OR INLET MUST BE ASSOCIATED WITH A BOX, A SLEEVE OR A HANDLE.

Voltage 50 Hz	Polarity	Part no.	Part no.	Part no.
220 - 250 V	1P+N+E	2664015	2666015	12-21 mm 2661015
380 - 440 V	3P+E	2664013	2666013	12-21 mm 2661013
380 - 440 V	3P+N+E	2664017	2666017	12-21 mm 2661017

► Other voltages, frequencies and contact configurations are available (see page 10).

BOXES

Ex metal cable gland included*



Wall box metal 90°

HANDLES

Ex metal cable gland included*



Straight handle metal


Cable gland entry	Part no.		Cable gland entry	Part no.	
M25	266AB5325M	9-16 mm	M25	266A95325M	9-16 mm
M32	266AB53	12-21 mm	M32	266A963	12-21 mm
M40	266AB5340M	16-27 mm	M40	266A95340M	16-27 mm

* For alternatives with Earth continuity, please contact us

LOCKING

Locking position connected or disconnected by lockable shaft as standard.

MARECHAL ELECTRIC MAROMME

 II 2 G D Ex de IIC tD A21

-40 °C ≤ Ta ≤ +60 °C T5 T90 °C

-40 °C ≤ Ta ≤ +50 °C T6 T80 °C

IECEX LCI 09.0015 / LCIE 04 ATEX 6038